



LISTING INFORMATION OF
**McKeon - SafeSpace™ SS500 Series Tornado & Hurricane
Resistant Door**

SPEC ID: 43799

CONFIDENTIAL
PROPERTY OF McKEON

McKeon Door Company
44 Sawgrass Drive
Bellport, NY 11713
United States

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

CONFIDENTIAL
PROPERTY OF McKEON

LISTING INFORMATION

McKeon SafeSpace™ SS500 Series Tornado & Hurricane Resistant Door

This listing is for wind pressure and impact resistance only. Fire resistance, when required by Section 601 of ICC 500-2014, is outside the scope of this listing. Assemblies required to be fire-resistance-rated shall also bear the label of a separate fire listing to the applicable standard(s).

ICC-500-2014 WIND PRESSURE AND IMPACT RATINGS

Assembly Type	Permitted Size	Tornado Resistance	Tornado Impact Rating
Roll-up Tornado Shelter Door	Min: 4'-4" wide* 4'-0" high Max: 16'-4" wide 18'-0" high	+252/-252PSF	100 MPH 15 lbs.
Configuration Mounted to the inside surface of a tornado shelter wall	Door: McKeon SafeSpace™ SS500 Series Tornado & Hurricane Resistant Door Upwardly acting roll-up door assembly with 3" steel slats and structural support guide system		

*Width is tip to tip of support guide angles

Assembly Type	Permitted Size	Hurricane Resistance	Hurricane Impact Rating
Roll-up Hurricane Shelter Door	Min: 4'-4" wide* 4'-0" high Max: 16'-4" wide 18'-0" high	+201 / -201 PSF	100 MPH 9 lbs.
Configuration Mounted to the inside surface of a Hurricane shelter wall	Door: McKeon SafeSpace™ SS500 Series Tornado & Hurricane Resistant Door Upwardly acting roll-up door assembly with 3" steel slats and structural support guide system		

*Width is tip to tip of support guide angles

Attribute	Value
Certificate Date of Expiry	April 23, 2025
Certificate Date of Initial Registration	April 23, 2020

Certificate Number	WHI20-20384307
Criteria	ICC-500 (2014)
CSI Code	08 34 00 Special Function Doors
Intertek Services	Certification
Issue Status	1
Listed or Inspected	LISTED
Listing Section	WIND LOAD RESISTANT DOORS
Report Number	H5680, F3964, E2664, G10337886, N0130, G104979545
Spec ID	43799
Test Original Issue Date	April 9, 2015
Verification Testing	No
Windload/Structural	Storm Shelter
Windload/Structural	Tornado Resistance

CONFIDENTIAL
PROPERTY OF McKEON